

**DP 2595 Closed Cell Foam Spray Adhesive** 

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

## Section 1 – Product And Company Identification

**Product identifier** Product Name: Closed Cell Foam Spray Adhesive Product Code: DP 2595

## Recommended use and restrictions on use

#### Recommended use Adhesive

Supplier's DetailsManufactured For:Design PolymericsAddress:3301 W. Segerstrom Ave., Santa Ana, CA 92704Information Phone:(714) 432-0600

#### **Emergency telephone number**

Chem-Tel: (800) 255-3924 (24 hours)

## Section 2 - Hazard Identification

### Hazard Classifications

Skin Irritation: Category 2 Eye Damage: Category 2A Carcinogenicity: Category 2 STOT Single Exposure: Category 3 Extremely Flammable Aerosol: Category 1

## Signal word

DANGER!

### Pictograms



Hazard Statements Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Contains gas under pressure; may explode if heated.

## **Precautionary Statements**

Do not handle until all safety precautions have been read and understood. IF exposed or concerned: Get medical attention. Avoid breathing vapors. Use in a well-ventilated area. IF INHALED: Call a doctor if you feel unwell. Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash skin with plenty of water. If skin irritation occurs: Get medical attention.



## DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021	<b>Version #:</b> 6.0	Supersedes Date: September 12, 2018
Potential Health Effects		
Principal Routes of Exposure:	Inhalation, skin absorption, eye contact.	
Acute Effects		
Eye:	Contact with eyes may cause irritation. Direc cause stinging, tearing, redness, swelling an	
Skin:	May cause skin irritation and/or dermatitis. Prolonged or repeated contact or exposure to vapors may cause redness, burning, and drying and cracking of skin.	
Inhalation:	Breathing high concentrations of vapors may signs of nervous system depression (e.g., he vomiting, loss of coordination and fatigue).	
Ingestion:	Ingestion may cause irritation of the digestive nervous system depression	e tract, nausea, vomiting, and signs of
Chronic Effects	Avoid repeated exposure. May cause blood allergic reactions in very susceptible persons	
Aggravated Medical Conditions	Pre-existing eye, skin or respiratory disorder product.	s may be aggravated by exposure to this

## Section 3 – Composition/Information on Ingredients

Ingredient	C.A.S. No.	% by Wt
Methylene Chloride	75-09-2	35-60%
Liquefied petroleum gas	68476-86-8	35-60%

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

## Section 4 – First Aid Measures

### General Advice:

Show this safety data sheet to the doctor in attendance.

### Eyes:

Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical attention.

### Skin:

Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash affected areas thoroughly with mild soap. If skin irritation persists, get immediate medical attention.

### Inhalation:

Move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen and get immediate medical attention.

## Ingestion:

Do not induce vomiting, seek immediate medical attention. If vomiting occurs, keep head lower than hips to prevent aspiration.

## Notes to Physician:

Treat symptomatically.



DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

## Section 5 – Fire-Fighting Measures

## Extinguishing Media

Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent containers cool; avoid spreading the liquid with water used for cooling. Water-based sprinkler systems may help contain larger fires.

## **Special Protective Equipment and firefighting procedures**

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### Specific hazards arising from the chemical.

Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning.

#### Section 6 – Accidental Release Measures

### **Personal Precautions**

Use personal protective equipment. Remove all sources of ignition.

## **Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

## Methods for Clean-up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## Other Information

None known.

## Section 7 – Handling and Storage

### Handling

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces, and sources of ignition.

### Storage

Keep containers tightly closed in a dry, cool, and well-ventilated place. Keep away from extremes of heat or cold. Keep in properly labeled containers.

## Section 8 – Exposure Controls/Personal Protection

**Note:** Any items listed in the above with workplace control parameters which are not listed in section 3 are below threshold reporting values.

REL - Recommended Exposure Limits TLV - Threshold Limit Value

### Exposure Limits

## Components with workplace control parameters:

Hazardous Components	OSHA PEL	ACGIH TLV
Methylene chloride	25	50
Liquefied petroleum gas	Not established	1000



DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

## Engineering Measures

Ensure adequate ventilation, especially in confined areas.

## Personal Protective Equipment:

Eyes/Face:

Safety goggles or glasses, or full-face shield.

## Skin:

Protective gloves and impervious clothing. Consult the glove/clothing manufacturer for proper selection of materials.

## Respiratory:

In operations where exposure limits are exceeded, use a NIOSH-approved respirator that has been selected by a technically qualified person for the specific work conditions.

## **Hygiene Practices:**

Avoid contact with skin, eyes, and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using, do not eat, drink, or smoke.

Section 9 – Physical and Chemical Properties			
Appearance	Amber-colored liquid	Upper Flammability/Explosive Limit	4.37
Oxidizing Properties	No Data Available	Lower Flammability/Explosive Limit	0.87
Odor	Characteristic odor	Vapor Pressure (mm Hg)	Not available
Odor Threshold	No Data Available	Vapor Density	Heavier than air
pH Value	No Data Available	Bulk Density (Ib/gal)	6.81
Melting Point / Freezing Point	No Data Available	VOC Content (g/L)	312
Boiling Point	-24.0 °F [-31.1 °C]	VOC Less Water & Exempts (g/L)	423
Flash Point	-156.0°F [-104.4°C]	Specific Gravity (g/l)	0.818
Explosive Properties	No Data Available	Auto-Ignition Temperature	No Data Available
Evaporation Rate	Faster than nBuAc	Decomposition Temperature	No Data Available
Flammability (solids)	No Data Available	Partition Coefficient	No Data Available
Solubility in Water	Insoluble	Viscosity	No Data Available

## Section 10 – Stability and Reactivity

## Chemical Stability:

Stable under normal conditions. Hazardous polymerization does not occur.

## Possibility of Hazardous Reactions:

None under normal conditions of use.

## **Conditions to Avoid:**

Keep away from open flames, hot surfaces, static electricity, and sources of ignition. Avoid extremes of heat or cold.

## Materials to Avoid:

Incompatible with strong acids and bases, alkali metals, halogens, and strong oxidizing agents.



DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

## Hazardous Decomposition:

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be formed during combustion.

## Section 11 – Toxicological Information

## Numerical Measures of Toxicity for Individual Components

## Likely Routes of Exposure:

Inhalation, skin absorption, eye contact.

Acute Toxicity	Oral: No data; Skin: No data;	Sensitization	Respiratory: No data; Skin: No
	Inhalation: No data		data
Irritation	Skin: Category 2	Mutagenicity	No data
Reproductive	No data	Aspiration	No data
Toxicity		Hazards	
Specific Target Orga	an Toxicity - Single Exposure	Category 3	
Specific Target Orga	Specific Target Organ Toxicity - Repeated Exposure No data		

### Chronic Toxicity / Carcinogenicity:

The information below indicates whether each agency has listed any ingredient as a carcinogen. If no ingredients are listed below, then there are no known classifications.

Component	IARC	NTP	OSHA
Methylene chloride	Listed	Listed	Listed

## Section 12 – Ecological Information

The information and data for components are listed individually for areas of ecological consideration below.

Aquatic Toxicity	Acute and prolonged toxicity to fish: Acute toxicity to aquatic invertebrates: Environmental fate and pathways:		s: No Data A	No Data Available No Data Available No Data Available	
Persistence and Degrada		No Data Available	Mobility in Soil	No Data Available	
Bioaccumulative Potentia		No Data Available	Other Adverse Effects	No Data Available	

## Section 13 – Disposal Considerations

## Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

### Section 14 – Transport Information

The shipping classification in this section is meant as a guide to overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.



DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

REGULATION

## DESCRIPTION

DOT

Proper Shipping NameCHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.Technical Name(PROPANE, BUTANE)Hazard Class2.1UN NumberUN3501Packing Group

Placards



ICAO / IATA IMDG / IMO No Data Available No Data Available

### Section 15 – Regulatory Information

## **US TSCA**

Yes. All components are listed or exempt.

## Canada DSL

Yes. All components are listed or exempt.

### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation	CAS Number	Weight %
Methylene chloride	75-09-2	35-60%

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

CAS Number 75-09-2

Chemical Designation	CAS Number	Weight %
Methylene chloride	75-09-2	35-60%

## State Regulations

### California Prop. 65

This product contains one or more chemicals known to the state of California to cause cancer and/or reproductive harm. Unless chemical names are listed below, these chemicals are present only in trace amounts. <u>www.P65Warnings.ca.gov</u>.

Chemical Name	
Methylene chloride	



DP 2595 Closed Cell Foam Spray Adhesive

Revision Date: May 25, 2021

Version #: 6.0

Supersedes Date: September 12, 2018

### Section 16 – Other Information

#### NFPA Hazard Classification Health: 2 Flammability: 3 Instability: 0 Special Hazards: B

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Creation Date:	May 15, 2015
Review Date:	September 21, 2018
Revision Date:	May 25, 2021. Supersedes all previous
Version #:	4.0
Revision Notes:	New formulation
Prepared By:	Technical Department

**Disclaimer:** The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.