

DP

# Seam Sealant

**A non-curing, non-skinning, solvent based pumpable butyl injection seam sealant ideal for sealing seams in Pittsburgh, Button Punch, Snap Lock and roll formed seams.**

## Recommended Uses:

- Pittsburgh duct seams.
- Snap Lock and Button Punch seams.
- Coil line application.
- Roll formed seams.
- Suitable for use on common construction materials including: steel, aluminum, masonry and wood.

## Features and Benefits:

- Permanently Flexible
- Non-Curing, Non-Skinning
- Non-Oxidizing
- Non-Corrosive
- Pumpable
- Withstands Joint Movement
- Excellent Water Resistance
- Excellent Cold Weather Flexibility

## Directions For Use:

**Uses:** DP Seam Sealant may be used in metal seams where a non-curing, permanently flexible seal is required. DP Seam Sealant is ideal for sealing Pittsburgh, Button Punch and Snap Lock longitudinal seams. It may also be used in pocket seams of roll formed metal connectors.

**Application:** DP Seam Sealant should be injected into seams, typically by pump. Since DP Seam Sealant does not cure, seams should be closed to prevent migration of sealant.

## Technical Data:

**Color:** Gray

**Chemical Family:** Butyl Rubber

**Odor:** Mild Solvent Odor

**Solids Content:** 90%

**Application Temperature:** 0°F - 100°F

**Storage Temperature:** 0°F - 100°F

**Service Temperature:** -40°F - 200°F

**Flash Point:** >100°F

**Pressure Classes:** Meets all SMACNA Pressure Classes

**Seal Classes:** Meets all SMACNA Seal Classes

**Shelf Life:** 2 Years

**Packaging:** 5 gallon pails and 54 gallon drums

ASTM E-84 SURFACE BURNING CHARACTERISTICS  
DP Seam Sealant applied to inorganic reinforced cement board  
Flame Spread: 0      Smoke Developed: 0  
Test as applied in one 0.38" wide strip at a thickness of 1/16" on center.  
Sealant coverage: 2.1% of the exposed test sample area.

TECHNICAL support bulletin



3301 W. Segerstrom Ave.  
Santa Ana, CA 92704  
Toll Free 800.641.0808  
Phone 714.432.0600  
Fax 714.432.0660  
[www.designpoly.com](http://www.designpoly.com)